

Complete with:

- Centaur 50-6201 Gas Turbine
 - Axial flow 11-stage comp/ratio: 10.6:1
 - Nominal flow: 18.8 kg/sec (41.4 lb/sec)
 - Annular Combustor – 12 Injectors – Dual Fuel
 - Output Speed: 14,951 rpm
- Reduction Drive Gearbox
 - Epicyclic Gear Configuration
 - Output Speed: 1,800 rpm
- Generator
 - KATO: 4,160 V, 659 A, 3 PH, 60 HZ, 4 P
 - Efficiency at 100% load: 96.8 % @ 0.8 PF; 97.3 % @ 1.0 PF
- Start System – Direct Drive Motor
- Lube Oil System – Duplex Onskid with DC Backup
- Fuel System – Liquid & Gas (changeable during operation)
- Package Configuration – Enclosed with Sound Attenuation (90 dBA @ 1m)
- Enclosure Ventilation System
- Controls System – Allen Bradley PowerFlex 700
 - Onskid HMI
 - Flex I/O
 - Integrated Bently Nevada Vibration System
- Fire & Gas Protection
 - Detronics Eagle Quantum Premier Controls
 - CO2 Suppression System with Cabinet
- Battery Charger – American Battery Charging 120V UPS
- Ancillary Equipment
 - Altair Self-Cleaning Air Filtration System
 - High-Ambient Oil Cooling System
 - Oil Mist Separator