



Surplus and Prime Worldwide

Ordering Information-Standard Horizontal and Vertical Housings

Part Number	No. Of Filters	Rated Flow Per Housing- GPM/LPM 60" Long Filter	Nominal Housing Diameter (in/mm) (D)	Inlet/Outlet Flange Diameter (in/mm)	Maximum* Horizontal Housing Overall Length (in/mm) (L)	Horizontal Housing Height (in/mm) (H)	Distance Between Housing and Lid and Tubesheet (in/mm)	Housing* Weight Empty (lbs/kg)	Housing* Weight Full Of Water (lbs/kg)	Housing Cover Swing Opening (in/mm)
1HF 0804F1	1	500/1893	9/219.1	4/101.6	89/2261	32/817	14.5/368.3	471/214	621/282	9.0/228.6
2HF 1606F1	2	1000/3785	16/406.4	6/152.4	100/2527	40/1023	22.7/576.3	1172/532	1771/803	25.8/654.6
3HF 1808F1	3	1500/5680	18/457.2	8/203.2	104/2642	43/1093	26.2/665.2	1583/718	2384/1081	27.3/692.8
4HF 2008F1	4	2000/7570	20/508.0	8/203.2	105/2654	46/1175	26.4/669.6	2087/947	3048/1382	29.8/756.3
7HF 2412F1	7	3500/13248	24/609.6	12/304.8	112/2832	59/1487	31.9/809.6	3250/1474	4762/2160	34.3/870.6
12HF 3016F1	12	6000/22710	30/762.0	16/406.4	121/3073	58/1480	38.7/982.7	4670/2118	7306/3314	38.0/964.9
19HF 3620F1	19	9500/35958	36/914.4	20/508.0	129/3264	68/1718	43.4/1101.6	7060/3202	11121/5045	44.8/1138.8

* For 60 inch filter lengths

Ordering Information - Horizontal Orientation, Centerpipe Designed Housings

Part Number	No. Of Filters	Rated Flow Per Housing- GPM/LPM 60 in Long Filter	Nominal Housing Diameter (in/mm) (D)	Inlet/Outlet Flange Diameter (in/mm)	Maximum* Horizontal Housing Overall Length (in/mm) (L)	Horizontal Housing Height (in/mm) (H)	Distance Between Housing and Lid and Tubesheet (in/mm)	Housing* Weight Empty (lbs/kg)	Housing* Weight Full Of Water (lbs/kg)	Housing Cover Swing Opening (in/mm)
7HF C 2808F-1	7	3500/13248	28/711	8/203.2	104.3/2648	57.0/1448	4.9/124	4056/1840	6229/2825	36/914
8HF C 3012F1	8	4000/15140	30/762	12/304.0	117.6/2988	58.3/1480	6.1/154	4707/2135	7348/3333	40/1018

* For 60 inch filter lengths

Code	Housing Configuration
H	Horizontal
V	Vertical

Code	Nominal Cartridge Length (in/mm)
2	20/508
4	40/1016
6	60/1524
8	80/3032

Code	Housing Metallurgy
285	Carbon Steel Vessel, 304 Stainless Steel Tubesheet
S3	304L Stainless Steel
S8	304 Stainless Steel
L3	316L Stainless Steel
L8	316 Stainless Steel

Code	Optional Outlet Size ¹ Horizontal Housings
XU	Upper Outlet Location
XL	Lower Outlet Location

¹ If the housing is to be used as a prefilter to a horizontal liquid/liquid coalescer, then the vessel should be ordered using the XU or XL option for the outlet location. The orientation of the outlet should be the same as that of the sump on the coalescer. In this way no buildup of coalesced liquid will occur in the prefilter.

Handwritten signature: Wade W...