



Surplus and Prime Worldwide

MATERIALS LIST INVENTORY

1,030												478.79
STT	Descriptions	Unit	Q'ty	OD		Length		Weight		Total Weight (Tons)	Status	
				mm	Thick (mm)	M	Ft	Pounds	Tons			
7"			241							125.08		
1	LANDING COLLAR JOINT 7" 29# SM80 VTOP HT, MAKE UP BAKER LOK WITH 7" LANDING COLLAR & 2 SPIRO LOCK	Jts	2	178	10.36	12	39.37	1,141.73	0.52	1.04	New	
2	CASING, 7"OD, VAM TOP HC CONNECTION, 32PPF, SUPER 13CR110 KSI, (2% MINIMUM MOLYBDENUM CONTENT), R3, SEAMLESS, 6 SPECIAL DRIFT, GAS TIGHT (METAL TO METAL PRIMARY SEAL). 100% COMPRESSION EFFICIENCY. MAXIMUM YIELD STRENGTH DE-RATING FACTOR @ 200 DEGC: 0.88 - 0.89.	Jts	1	178	11.51	12	39.37	1,259.84	0.57	0.57	New	
7	CASING, SLOTTED 7" OD, 29 PPF, JFEBEAR CONNECTION, 13%CR-L80, R3.	Jts	30	178	10.36	12	39.37	1,141.73	0.52	15.54	New	
17	X-OVER, 7"OD, HYD513 PIN CONNECTION X BTC BOX CONNECTION, 32PPF, P110. LG: 12MTR	Ea	2	178	11.51	12	39.37	1,259.84	0.57	1.14	New	
16	X-OVER, 7"OD, VAMTOP HC PIN CONNECTION X BTC BOX CONNECTION, 32PPF, P110. LG: 12 MTR	Ea	2	178	11.51	12	39.37	1,259.84	0.57	1.14	New	
1	CASING, 7"OD, HYDRIL563 CONNECTION, 29PPF, P110, R3	Jts	204	178	10.36	12	39.37	1,141.73	0.52	105.65	New	

20" (508mm)			100							276.13	
3	CONDUCTOR PIPE, 20" OD X 1.250" W.T. (250.3 PPF) API-5L, X-56, SAW, R3, WITH SWITH DW2AR, DOUBLE SEAL (95 KSI) BOX UP X PIN DOWN, C/W PROTECTOR, O-RING, ANTI-ROTATION KEY (COATED)	Jts	20	508	31.75	12	39.37	9,854.33	4.47	89.40	New
8	CASING, 20"OD X 0.625"WT, API 5L X56, SWIFT DW2 AR BOX UP X PIN DOWN, R3 (OSI SUPPLY PIPE)	Jts	70	508	15.88	12	39.37	5,177.17	2.35	164.38	New
14	PUP JOINTS, 20" OD X 1.250" W.T. (250.3 PPF) API 5L, API 5L, X-56, SAW, 6M LENGTH, WITH SWITH DW, 2AR, DOUBLE SEAL (95 KSI) BOX UP X PIN DOWN C/W PROTECTOR, O-RING, ANTI-ROTATION KEY (COATED)	Ea	10	508	31.75	6	19.69	4,927.17	2.23	22.35	New
Ong 30" (762mm)			7							35.98	
21	CONDUCTOR,DLINE RUNNING JOINT, ST2 PIN X MMR PIN, 30"OD X 1"WT, X-52, R3, C/W PROTECTOR.	Jts	3	762	25.40	12	39.37	12,204.72	5.54	16.61	New
23	LANDING JOINT, 30"OD, LEOPARD SDDS CONNECTION BOX X DMR-T PIN. LG: 6M	Jts	1	762	25.40	6	19.69	6,102.36	2.77	2.77	New
25	CONDUCTOR, X-OVER, 30"OD ST-2 PIN UP X DMR PIN DOWN	Jts	1	762	25.40	12	39.37	12,204.72	5.54	5.54	New
139	CONDUCTOR, MUD LINE JOINT, 30" DMR BOX UP X ST2 BOX DOWN R49229-2	Jts	2	762	25.40	12	39.37	12,204.72	5.54	11.07	New
9 5/8" (245mm)			10							5.92	
5	INTERMEDIATE JOINT 9-5/8" VAM TOP 53.5PPF C110	Jts	2	244	13.84	12	39.37	2,106.30	0.96	1.91	New
15	PUP JOINT, 9-5/8"OD, TSH BLUE CONNECTION, 53.5PPF, TN 110SS, (SOUR SERVICE), SEAMLESS, (SPECIAL DRIFT: 8-1/2"). LG: 6M	Ea	1	244	13.84	6	19.69	1,053.15	0.48	0.48	New
18	X-OVER, 9-5/8"OD, HYDRIL 563 BOX X JFE-BEAR PIN, 47PPF. LG:+/-6MTR	Ea	4	244	11.99	6	19.69	925.20	0.42	1.68	New

120	CASING HANGER , SD-1 CASING HANGER ASSEMBLY, 30" X 13-3/8", MAX OD OF SUPPORT RING IS 26.805", MAX LOAD CAPACITY OF 2 MILLIONS LBS, FORGED AISI 4140 ALLOY STEEL OR EQUIVALENT BODY MATERIAL , (UPPER AND LOWER METAL-TO-METAL SEAL PROFILES, POSITIVE STOP SHOULDER PREVENTS OVER TORQUING OF METAL-TO-META	Ea	1						
121	CASING HANGER , SD-1 CASING HANGER ASSEMBLY, 30" X 13-3/8", MAX OD OF SUPPORT RING IS 26.805", MAX LOAD CAPACITY OF 2 MILLIONS LBS, FORGED AISI 4140 ALLOY STEEL OR EQUIVALENT BODY MATERIAL , (UPPER AND LOWER METAL-TO-METAL SEAL PROFILES, POSITIVE STOP SHOULDER PREVENTS OVER TORQUING OF METAL-TO-META	Ea	1						
122	CASING HANGER, SD-1 CASING HANGER ASSYEMBLY, 13-3/8" X 9-5/8" , MATERIAL CLASS: DD, PSL2, TEMP CLASS: U, H2S SERVICE, (UPPER AND LOWER METAL-TO-METAL SEAL PROFILES, POSITIVE STOP SHOULDER PREVENTS OVER TORQUING OF METAL-TO-METAL SEAL, INTERNAL LEFT HAND THREAD FOR LANDING SUB (RUNNING TOOL), INTERNA	Ea	1						

New
New
New

165	X-OVER, 2-7/8" HT PAC BOX X 2-7/8" 6.4PPF, HYDRILL 511 PIN, 3-1/8"OD X 1-1/2"ID x 24" LONG OVERALL, PIN END ID BORED TO 2.377"	Ea	3								New
166	X-OVER, 2-7/8" HT PAC BOX x 2-7/8" CS, HYDRILL PIN, 3-1/8"OD x 1-1/2"ID x 24" LONG OVERALL, PIN END ID BORED TO 3.210".	Ea	1								New
TOTAL			1,030								



Surplus and Prime Worldwide